

4-20-00

A

Case Docket No. PHB 34, 339

THE COMMISSIONER OF PATENTS AND TRADEMARKS, Washington, D.C. 20231

Enclosed for filing is the patent application of Inventor(s):
PAUL BUCKNELL, TIMOTHY J. MOULSLEY

For: RECONFIGURABLE COMMUNICATION NETWORK

ENCLOSED ARE:

- ☒ Appointment of Associates;
☒ Information Disclosure Statement, Form PTO-1449 and copies of documents listed therein;
☒ Preliminary Amendment;
☒ Specification (14 Pages of Specification, Claims, & Abstract);
☒ Declaration and Power of Attorney:
 (1 Page of a ☒ fully executed ☐ unsigned Declaration);
☒ Drawing (2 sheets of ☐ informal ☒ formal sheets);
☒ Certified copy of GREAT BRITAIN application Serial No. 9909275.1;
☒ Authorization Pursuant to 37 CFR §1.136(a)(3)
☐ Other: ;
☒ Assignment to U.S. PHILIPS CORPORATION.

FEE COMPUTATION

CLAIMS AS FILED				
FOR	NUMBER FILED	NUMBER EXTRA	RATE	BASIC FEE - \$690.00
Total Claims	9 - 20 =	0	X \$18 =	0.00
Independent Claims	5 - 3 =	2	X \$78 =	156.00
Multiple Dependent Claims, if any			\$260 =	0.00
TOTAL FILING FEE				= \$846.00

Please charge Deposit Account No. 14-1270 in the amount of the total filing fee indicated above, plus any deficiencies. The Commissioner is also hereby authorized to charge any other fees which may be required, except the issue fee, or credit any overpayment to Account No. 14-1270.

☐ Amend the specification by inserting before the first line as a centered heading --Cross Reference to Related Applications--; and insert below that as a new paragraph --This is a continuation-in-part of application Serial No. , filed , which is herein incorporated by reference--.

CERTIFICATE OF EXPRESS MAILING

Express Mail Mailing Label No. EL335550488US

Date of Deposit April 19, 2000

I hereby certify that this paper and/or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 C.F.R.

1.10 on the date indicated above and is addressed to the Commissioner of Patents and Trademarks, Washington, D.C. 20231.

Natale A. Manzo
Typed Name

Natale A. Manzo
Signature

Dicran Halajian
Dicran Halajian, Reg. 39,703
Attorney
(914) 333-9607
U.S. Philips Corporation
580 White Plains Road
Tarrytown, New York 10591

\\SERVER0\SYS2\WPDOCS\HJ\MT13HJA1.MA0.doc

04/19/00
jc544 U.S. PTO

jc135 U.S. PTO
09/552650
04/19/00

04/19/00 04:44:00

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of

Atty. Docket

BRIAN BUCKNELL ET AL.

PHB 34,339

Serial No.

Filed: CONCURRENTLY

Title: RECONFIGURABLE COMMUNICATION NETWORK

Honorable Commissioner of Patents and Trademarks
Washington, D.C. 20231

PRELIMINARY AMENDMENT

Sir:

Prior to calculation of the filing fee and
examination, please amend the above-identified application
as follows:

IN THE CLAIMS

Claim 3, line 1, delete "or 2"

Claim 4, line 1, delete "2 or 3,"


Claim 8, line 1, delete "6 or 7,"

REMARKS

The claims have been amended to delete multiple dependencies.

The within amendment is limited to the equivalent of cancellation of claims, and pursuant to MPEP §506, should be entered prior to calculation of the fee.

Respectfully submitted,

By 
Dicran Halajian, Reg. 39,703
Attorney
(914) 333-9607
April 13, 2000

DESCRIPTION

RECONFIGURABLE COMMUNICATION NETWORK

5 The present invention relates to a configurable/reconfigurable communication network which is, or terminals of which are, configurable or reconfigurable in response to data transmitted for example by corded or cordless, say over-the-air, link.

10 It is known from Philips Telecommunication Review, Vol. 41, No. 1, April 1983 "FM-900 series of VHF/UHF mobile radio telephone equipment" by F.P. van Enk, pages 36 to 45 to provide mobile radio units with microprocessors and a central control PROM (programmable read only memory) whereby personality data associated with a channel number can be stored. As a
15 consequence, when a user selects a channel, the mobile radio unit adapts itself in accordance with the stored data so that it is ready to operate without any further intervention by the user. Such a radio unit requires the PROM to be programmed using an external programmer.

20 It is also known to supply data, such as receiver identity codes, to digital pagers by over-the-air transmissions.

25 In the field of telecommunications, particularly digital paging, in order to enable a user to roam in different geographical areas which operate different systems and/or different characteristics it was necessary for a traveller to carry two or more portable units, each of the portable units being configured to operate in a respective area. One proposal for avoiding the need to carry several portable units is disclosed in European Patent EP-B-0 538 933. The portable unit is able to be reconfigured in response to data downloaded from a device, for example a plastics card carrying the data, inserted in an aperture or slot and read by the portable unit.

30 In view of the plethora of communications standards in force and coming into force it is desirable for equipment at each end of a link to be compatible.

According to a first aspect of the present invention there is provided a method of operating a radio system comprising first and second terminals, the method comprising configuring/reconfiguring one of said first and second terminals by a process of service negotiation with the other of said first and second terminals.

More particularly the first aspect of the present invention provides a method of operating a radio system comprising first and second terminals, the method comprising one of said first and second terminals transmitting a message giving parameters relating to its capabilities, and the other of the first and second terminals receiving the message and configuring/reconfiguring itself in accordance with the received parameters.

According to a second aspect of the present invention there is provided a communications system comprising first and second terminals which are able to communicate with each other, wherein at least one of the first and second terminals has means for configuring/reconfiguring itself by a process of service negotiation.

The second aspect of the present invention also provides a communications system comprising first and second terminals which are able to communicate with each other, wherein at least one of the first and second terminals has means for configuring/reconfiguring itself in response to the receipt of a message transmitted by said other of the first and second terminals giving parameters relating to its capabilities.

According to a third aspect of the present invention there is provided a terminal for use in a communication system in which one terminal can configure/reconfigure another terminal by service negotiation, the terminal comprising a transceiver, a memory for storing software functions, and a processor for controlling the operation of the terminal in accordance with stored software functions, at least one of the software functions being alterable in response to the receipt of a message containing the new software function plus interface software required by the processor in building a new function into an actual implementation on the terminal.

The present invention is based on the concept that the primary station (or fixed terminal) can adapt itself in response to software (or other information) relayed over a communications link by a secondary station (or mobile terminal), and vice versa. Thus provided that the primary station or
5 secondary station is capable of adapting or configuring/reconfiguring itself, it is possible for a range of equipments to be able to operate on a network without having to be set-up in advance in a factory. This is of particular importance when the same piece of equipment has to be capable to operate not only with different radio interfaces, protocols, compress/decompression algorithms and
10 applications but also it has to be able to be agile in its operation to suit the prevailing radio environment.

An application running on a mobile terminal (or secondary station) and requiring communications facilities will normally need to establish a connection with another (peer) application on a remote terminal (or equivalent). The
15 network may offer a standardised service tailored for the application and thus provide a communication channel with appropriate properties, for example (bit rate, delay, error rate and so forth). However, it may be that the application will be unknown to the network, and therefore the "nearest" suitable service could be offered. This would require some negotiation to take place between
20 the terminal and network on the required and available link parameters. In another application the terminal may take an active part in configuring/reconfiguring the network to provide the required communications facilities.

In a radio system it is usually desirable to jointly optimise the source
25 and channel coding. Therefore, if the source coding algorithm is unknown to the network, it is likely that the associated channel coding will also be unknown. Therefore the necessary information must be provided to the network to allow implementation of an effective solution. The same argument can be applied to the modulation scheme.

30 In some cases there may be more than one network involved in setting up a connection. Then the properties of each link should be considered, as well as the overall performance.

The uploading could be between terminals, for example to ensure that the applications at both ends of the link are compatible.

The present invention will now be described, by way of example, with
5 reference to the accompanying drawings, wherein:

Figure 1 is a general diagram of a cordless/cellular telephone system,

Figure 2 illustrates in block schematic form the software architecture of a reconfigurable DECT (Digitally Enhanced Cordless Telephone), fixed part and portable part, and

10 Figure 3 is a diagram of the software download procedure.

In the drawings the same reference numerals have been used to indicate corresponding features.

Referring to Figure 1, the communication system comprises a fixed part
15 (or fixed terminal) FP and two portable parts (or mobile terminals) PP1, PP2. The fixed part FP comprises a network controller 10 which is effectively a large computer and which is coupled to a radio transceiver 12. An antenna 14 is coupled to the transceiver 12. Each of the portable parts PP1, PP2 comprises an antenna 20 coupled to a radio transceiver 22. A processor 24 having an
20 EPROM 26 for storing configuration data is coupled to the transceiver 22.

For convenience of description, the illustrated system operates in accordance with the DECT (Digitally Enhanced Cordless Telephone) Standard. DECT is a TDMA standard comprising ten frequency channels, each channel being divided in the time domain into frames and each frame
25 comprises 24 time slots, 12 being transmit time slots (or simplex physical channels) and 12 being receive time slots (or simplex physical channels). Correspondingly numbered transmit and receive time slots constitute a duplex voice pair.

As is known in the art DECT operates in accordance with a layered
30 structure which comprises a Physical (PHL) layer, a Medium Access Control (MAC) layer, a Data Link Control (DLC) layer and a Network (NWK) layer. Some of the features of the PHL layer have been described in the previous

paragraph. Of the other layers the MAC layer is of interest. The MAC layer specifies the broadcast message control service, the connectionless message control service and the multibearer control service. The MAC layer also specifies the logical channels and how they are multiplexed and mapped onto the physical channels. More particularly the MAC layer performs two main functions, firstly it selects physical channels, and then establishes and releases connections on those channels. Secondly it multiplexes (and demultiplexes) control information, together with higher layer information and error control information, into slot-sized packets. In the interests of brevity the DLC and NWK layers will not be described.

Referring to Figure 2, there is shown the software architecture of a DECT based reconfigurable fixed part (or base station) FP and portable part (or mobile terminal) PP. The respective software architectures are mirror images of each other and for convenience of description the fixed part FP will be described and the same reference numerals shown with a prime will be used to refer to the corresponding features in the portable part PP.

The FP software architecture comprises the Physical (PHL) layer 30, the MAC layer 32, a C-plane (or control plane) 34 and U-plane (or user plane) 36 interface with the MAC layer 32. A configuration application 42 interfaces with a configuration manager 40 which is attached to a lower layer management entity (LLME) 38. The process is controlled by the configuration application 42 which is a high-level user interface application running as a user application. This enables the PP or FP to access Internet based servers for the retrieval of software. Application Program Interfaces (APIs) are used to allow generic elements to be used on different manufacturers' equipment.

The configuration manager 40 has three main options which are (1) take one module out and replace with another while the software is running, so called "Hot swapping", (2) run and test a new stack simultaneously with the currently used stack prior to changing-over stacks, so called "parallel stack operation, and (3) stop a protocol stack, compile a new downloaded function, test the new function and established a new connection, so called "stop and

start". Option (3) is the simplest option and the one that is more likely to be used in practice.

In the case of the FP being reconfigured in response to proposals from the PP, the following software uploading is proposed.

5 (1) Negotiation of features. A dialogue between the PP and FP to ensure that both are aware of the relevant capabilities of the other. For example, PP may be interested in the end-to-end delay offered by the connection to the fixed network, or the bit error rate or packet loss rate in an ATM connection. There may also be a need for negotiation between
10 terminals.

(2) Error handling. When a radio link is involved coding is likely to be a required for error detection and/or correction. The details of the coding (and interleaving) could be uploaded by the PP to the radio access part of the network (parameters or algorithm description). Similarly, decoding algorithms
15 could be specified. Error detection and concealment mechanisms could be specified. Error concealment is applicable in real-time voice and video transmission. It could also be implemented at the end destination, and could include filling in missing data based on interpolation, or repetition of previous data, or in the case of speech, muting.

20 (3) Specialised automatic repeat request (ARQ) algorithms (or information specifying them) could be loaded into the network by the PP. This may be appropriate if real-time delay constraints need to be met, or to ensure efficient use of the communication channel (e.g. for large packets).

25 (4) Non standard modulations could be specified and algorithms provided to generate/demodulate them.

(5) Agents could be loaded into the network to handle communications issues on behalf of the user. Some examples include: transcoding (e.g. where the applications use different source coding algorithms), monitoring delay and quality of service.

30 (6) Specialised algorithms for packet handling could be specified (e.g. dealing with packet priorities, packet dropping under congested conditions).

(7) Encryption/decryption/electronic signature/watermarking algorithms could be uploaded to the FP by the PP.

The method and system in accordance with the present invention contemplates the possibility of the FP or PP being configured or reconfigured by software relayed by the other part. Apart from the changes already mentioned, the following elements may be reconfigured:

(a) Changing the mode of operation of a FP to a PP and vice versa which may be desirable in certain situations to cover short-lived events.

(b) In the case of the physical channel:

(1) Changing from single slot to multiple-slot (number of bearers of the physical channel) and vice versa.

(2) Changing the frame structure.

(3) Altering the Cyclic Redundancy Check (CRC) scheme.

(4) Changing or altering power control algorithms (not applicable to all cordless or cellular systems some of which, such as DECT, do not have provision for power control).

(c) Changing elements of the MAC layer software functionality:

(1) Altering the higher layers error control.

(2) Altering the Radio Signal Strength Indicator (RSSI) scheme.


(3) Altering the Automatic Repeat Request (ARQ) Scheme.

(4) Altering handover algorithms.

Thus it is possible to take a non-configured terminal or a configured terminal and to configure or reconfigure it with a desired profile. Configuration or reconfiguration can either be manual or automatic, for example link adaptation in difficult channel could occur automatically. To effect configuration or reconfiguration, a terminal may comprise a Field Programmable Gate Array (FPGA), a programmable processor or a dedicated Application Specific Integrated Circuits (ASICs) designed to operate differently dependent on external influences.

The method in accordance with the present invention is facilitated by the transfer of key parameters from one terminal to the other terminal about it's

capabilities. Capabilities include the actual functions which are executed when a communications link is used. They include modulation type, bit rate, spreading codes (CDMA), number of carriers (OFDMA), etc. as well as the ability to accept new functions e.g. a new modulation scheme. Armed with the capability information the base station then selects the most appropriate software to download (or upload) from the mobile. This software does not have to contain actual code which is run on either one of the terminals, that is the PP or FP, it could be purely configuration information. As an example the following message sequence chart shows how a flexible air interface could be set up between a PP and FP. In this example the PP communicates it can transmit and receive RF modulation of any of three types (BPSK, QPSK and DQPSK), the FP can decide which modulation type is used, and instruct the PP to do so, by transferring a simple code which refers directly to the chosen modulation type.



This configuration of the air interface permits a simple testing of the air interface to be included in which a call is set up to exercise the physical layer and assesses the potential quality of service (QoS) for the link. Thus the air interface is tested to ensure that configuration has taken place without error.

5 The testing scheme comprises the transmission of a known test pattern of data, which is generated by the FP and known "a prioria" by the PP.

 The flexible air interface allows the adoption of adaptive spectrum management, where the FP can allocate different amount of spectrum to users dependant not only on the demands of the mobiles, but on the optimum usage
10 of the available spectrum.

 Caching can be used for frequently selected software upgrades.

 In order to give another illustration of the method in accordance with the present invention, an example will be given of a series of events for reconfiguration of the CRC.

- 15 1. Decide to reconfigure the PP's or FP's CRC scheme in MAC layer.
2. Interrogate MAC layer of PP or FP to be programmed for software MAP.
3. Use built-in rules to discover if the PP or FP can have it's CRC
20 scheme changed.
4. If change is possible, then download to PP or FP either:
- New parameters for CRC scheme, or
 - new CRC scheme source code.

 To reduce the amount of over the air transmission only the required
25 function is transmitted plus any interface software required in building the new function into the actual implementation of the FP or PP. For example if the implementation was on an FPGA, then a compiler for the specific FPGA would also be required.

5. If source code, the PP or FP configuration manager 40 (Figure 2)
30 compiles a link-able binary, the compiler is a custom coded compiler specific for a particular platform. After compilation, the binary is linked in with other software. The software can run on a programmable

processor or on a dedicated ASIC or could also be used to configure an FPGA implementing the new function. One method of software reconfiguration would be to define an area of memory accessed by the processor that is used for a particular function, this area could be replaced when a new function is downloaded.

6. If parameters, then update parameter storage locations
7. Run a test program which tests the new configuration
8. Setup a new call with newly reconfigured PP or FP

Referring now to Figure 3, this shows a typical generic software transfer from a Software Defined Radio (SDR) server 50 to a SDR terminal 51, either a PP or FP.

The transfer takes place in a number of phases.

Initiation:

In step 52, the server 50 initiates a download request.

In step 53, the terminal 51 acknowledges the download request.

Mutual Authentication:

In step 54, the server 50 authenticates the terminal 51.

In step 55, the terminal 51 authenticates the service provider and network operator.

Capability Exchange:

In step 56, the server 50 requests the terminal 51 to transmit its capability data.

In step 57, the terminal 51 transmits its capability response.

In step 58, the server 50 selects the appropriate software entities and parameter sets to match the capability of the terminal 51 and opens a download channel. (If no matching set of parameters exist, the operation is terminated). Transmit download installation profile.

Download Acceptance Exchange:

In step 60, the server 50 transmits Download Installation Profile.

Download Acceptance Exchange:

In step 59, the terminal 51 selects the installation options and also accepts or rejects the terms. In step 60, the server 50 validates the selected options.

Software Download:

5 In step 62, the server 50 downloads code modules including capability tables and delivery wrappers for each entity procedure.

In step 63, the terminal 51 tests the delivery integrity. Also it requests retransmissions as appropriate.

In step 65, the terminal 51 acknowledges safe receipt.

10 In step 64, the server 50 terminates the downloading.

Although the present invention has been described with respect to DECT, it is equally applicable to other one or two-way communication systems having a radio interface, a corded/landline interface or a combination of both between the PP and FP. In the case of a one-way communication system, control signalling is two-way and the system may be implemented using a
15 separate one-way communications system for example a DAB (digital audio broadcasting) system with a GSM two-way control channel.

In the present specification and claims the word "a" or "an" preceding an element does not exclude the presence of a plurality of such elements. Further,
20 the word "comprising" does not exclude the presence of other elements or steps than those listed.

From reading the present disclosure, other modifications will be apparent to persons skilled in the art. Such modifications may involve other features which are already known in the design, manufacture and use of
25 reconfigurable communication networks/terminals therefor and which may be used instead of or in addition to features already described herein.

CLAIMS

1. A method of operating a radio system comprising first and second terminals, the method comprising configuring/reconfiguring one of said first and second terminals by a process of service negotiation with the other of said first and second terminals.

2. A method of operating a radio system comprising first and second terminals, the method comprising one of said first and second terminals transmitting message giving parameters relating to its capabilities, and the other of the first and second terminals receiving the message and configuring/reconfiguring itself in accordance with the received parameters.

3. A method as claimed in claim 1 or 2, characterised in that the one of said first and second terminals initiating the configuring/reconfiguring operation transmits the required function plus software required in building a new function into an actual implementation on the other of said first and second terminals.

4. A method as claimed in Claim 1, 2 or 3, characterised by testing the air interface to ensure that configuration/reconfiguration has taken place without error.

5. A communications system comprising first and second terminals which are able to communicate with each other, wherein at least one of the first and second terminals has means for configuring/reconfiguring itself by a process of service negotiation.

6. A communications system comprising first and second terminals which are able to communicate with each other, wherein at least one of the first and second terminals has means for configuring/reconfiguring itself in

response to the receipt of a message transmitted by said other of the first and second terminals giving parameters relating to its capabilities.

7. A communications system as claimed in claim 6, characterised in
5 that the first and second terminals are radio terminals.

8. A communications system as claimed in claim 5, 6 or 7,
characterised in that the first and second terminals each have a software
interface including a memory and means for altering the memory, in that at
10 least a portion of the area of the memory has a part allocated to respective
software functions and in that the memory altering means replaces the area of
a respective part in response to a new function being downloaded.

9. A terminal for use in a communication system in which one
15 terminal can configure/reconfigure another terminal by service negotiation, the
terminal comprising a transceiver, a memory for storing software functions,
and a processor for controlling the operation of the terminal in accordance with
stored software functions, at least one of the software functions being alterable
in response to the receipt of a message containing the new software function
20 plus interface software required by the processor in building a new function
into an actual implementation on the terminal.

ABSTRACT

A RECONFIGURABLE COMMUNICATION SYSTEM

5 A communication system comprises first and second terminals(FP, PP) which are able to communicate at least control messages to each other. At least one of the first and second terminals has means for configuring/reconfiguring itself by a process of service negotiation with the other of the first and second terminals.

10 Each of the terminals comprises a transceiver, a memory for storing software functions, and a processor for controlling the operation of the terminal in accordance with stored software functions. At least one of the software functions is alterable in response to the receipt of a control message containing the new software function plus interface software required by the
15 processor in building a new function into an actual implementation on the terminal.

 The communication system may be a cordless and/or cellular telephone system in which the configuration/reconfiguration messages are sent over-the-air or a corded system in which configuration/reconfiguration messages are
20 relayed by landline.

(Figure 2)




FIG. 1




FIG. 2




FIG. 3

DECLARATION AND POWER OF ATTORNEY

Sole/Joint

Attorney's Docket No:
PHB34339US

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

RECONFIGURABLE COMMUNICATION NETWORK

the specification of which (check one)

☒ is attached hereto

☐ was filed on _____ as Application Serial No: _____ and was amended on _____

(if applicable).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, §1.56 (a).

I hereby claim foreign priority benefits under Title 35, United States Code, §119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed.

PRIOR FOREIGN APPLICATION(S)

COUNTRY	APPLICATION NUMBER	DATE OF FILING (day, month, year)	PRIORITY Claimed Under 35 U.S.C. 119
GREAT BRITAIN	9909275.1	23-04-1999	Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>
			Yes <input type="checkbox"/> No <input type="checkbox"/>

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35 United States Code §112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, §1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application.

PRIOR UNITED STATES APPLICATION(S)

APPLICATION SERIAL NUMBER	FILING DATE	STATUS (PATENTED, PENDING, ABANDONED)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. (list name and registration number)

Jack E. Haken, Reg. No 26,902
Algy Tamoshunas, Reg. No 27,677

SEND CORRESPONDENCE TO: Corporate Patent Counsel U.S. Philips Corporation 580 White Plains Road Tarrytown, New York 10591	DIRECT TELEPHONE CALLS TO: (Name and telephone number) (914) 332-0222
---	---

Dated: 25 FEB 2000		Inventor's Signature: Paul BUCKNELL	
FULL NAME OF INVENTOR	Last name BUCKNELL	First Name Paul	Middle Name
RESIDENCE & CITIZENSHIP	City BRIGHTON	State or Foreign Country ENGLAND	Country of Citizenship GREAT BRITAIN
POST OFFICE ADDRESS	Street & No 1, KEMPSTOWN MEWS	City BRIGHTON	State or Country GREAT BRITAIN Zip Code BN2 1SP

Dated: 25 Feb 2000		Inventor's Signature: Timothy J. Moulsey	
FULL NAME OF INVENTOR	Last name MOULSLEY	First Name Timothy	Middle Name J.
RESIDENCE & CITIZENSHIP	City CATERHAM	State or Foreign Country ENGLAND	Country of Citizenship GREAT BRITAIN
POST OFFICE ADDRESS	Street & No 2 WHYTELEAF ROAD	City CATERHAM	State or Country GREAT BRITAIN Zip Code CR3 5EE

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of

Atty. Docket

PAUL BUCKNELL ET AL.

PHB 34,339

Serial No.

Group Art Unit

Filed: CONCURRENTLY

Examiner:

Title: RECONFIGURABLE COMMUNICATION NETWORK

Honorable Commissioner of Patents and Trademarks
Washington, D.C. 20231

APPOINTMENT OF ASSOCIATES

Sir:

The undersigned Attorney of Record hereby revokes all prior appointments (if any) of Associate Attorney(s) or Agent(s) in the above-captioned case and appoints:


DICRAN HALAJIAN

(Registration No. 39,703)

c/o U.S. PHILIPS CORPORATION, Intellectual Property Department, 580 White Plains Road, Tarrytown, New York 10591, his Associate Attorney(s)/Agent(s) with all the usual powers to prosecute the above-identified application and any division or continuation thereof, to make alterations and amendments therein, and to transact all business in the Patent and Trademark Office connected therewith.

ALL CORRESPONDENCE CONCERNING THIS APPLICATION AND THE LETTERS PATENT WHEN GRANTED SHOULD BE ADDRESSED TO THE UNDERSIGNED ATTORNEY OF RECORD.

Respectfully,



Jack E. Haken, Reg. 26,902
Attorney of Record

Dated at Tarrytown, New York
this 13TH day of April, 2000.

S:\HJ\mt13hje1.ma0.doc